

**NS-100 Series, Dual Output, 100Watt**
**FEATURES:**

- ✓ Input voltage range 85-132VAC/180-264VAC
- ✓ High reliability
- ✓ Built-in EMI filter
- ✓ Short circuit, over current, over voltage protections
- ✓ Cooling by free air convection
- ✓ 100% burn-in test
- ✓ With LED power indicator
- ✓ 4 year warranty



Model	Input voltage (Vac)	Output voltage (Vdc)	Output current (A)	Efficiency Typ.
NS100-B1	85-132/	5, 12	10, 4	75%
NS100-B2	180-264	5, 24	10, 2	75%

Note: 90-132VAC/180-264VAC or 240-370VDC(Auto selectable), 50/60Hz(47-440Hz)

**ELECTRICAL**

Input						
Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units
Input voltage	$V_{in}$	--	85	--	132	Vac
			180	--	264	Vac
			240	--	370	Vdc
Input frequency	$F_{line}$	--	47	--	63	Hz
Inrush current	$I_{inrush}$	Cold start, $V_{in} = 115V_{ac}$ , full load	--	20	--	A
		Cold start, $V_{in} = 230V_{ac}$ , full load	--	40	--	A
Input current	$I_{in}$	Full load, $V_{in} = 115V_{ac}$	--	2.4	--	A
		Full load, $V_{in} = 230V_{ac}$	--	1.4	--	A

**NS-100 Series, Dual Output, 100Watt**
**ELECTRICAL**
**Output**

Parameters	Symbols	Test Conditions / Comment	Min.	Typ.	Max.	Units
Line regulation	$V_{out-line}$	$V_{in}$ from 100 Vac To 240 Vac	--	1	--	%
Load regulation	$V_{out-load}$	$I_{out}$ from min. To max.	--	1	--	%
Hold-on time	$T_{on\_hold}$	Full load, $V_{in}=115Vac$	--	17	--	ms
Turn-on rise time	$T_{on\_rise}$	Cold start, power on	--	--	500	ms
Ripple & noise	$V_{ripple}$	--	--	120	150	mVp-p

**Protection**

Over current	Type: works at over 105%; it will recover automatically after fault condition is removed
Short circuit	Hiccup mode, it will recover automatically after fault condition is removed
Over voltage	Type: 110-150%; Locked mode, it will recover automatically after turn off the power

**Environment**

Storage	$T_{storage}$	Humidity: 5% RH to 95% RH	-20	--	+75	°C
Ambient operating temperature	$T_a$	Startup at rated voltage (Required Derating)	-10	--	+70	°C
Operating relative humidity	$H_a$	Non condensing	10	--	95	%
MTBF	$T_{MTBF}$	Full load, 230Vac input, 25°C ambient temperature	--	--	200	kHrs
Dimension(LxWxH)	175 x 81.2 x 45mm					

**Safety / EMC**

Withstand voltage	I/P-O/P: 3KVac	I/P-FG: 2KVac	O/P-FG: 0.5KVac
Safety standards	CE, CB		
EMC	EN55022 Class B		

**Notes: 1. Rated Load and Rated Input Voltage,  $T_a=25^{\circ}C$ ;**

**2. Ripple & Noise are measured at 20MHZ of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uF & 47uF parallel capacitor.**

## NS-100 Series, Dual Output, 100Watt

### MECHANICAL

