

# HIGH CURRENT TOROID INDUCTORS FA2111HT-V&H SERIES



## FEATURES:

DC/DC converter, EMI filter applications.  
Low radiation.  
Low core loss.  
Test Frequency Response: 1KHz, 0.3mV.  
High current capacity.  
Operating temperature: -55°C to +105°C.  
Current to cause 50°C Max. temperature rise.

## PRODUCT IDENTIFICATION:


2111HT V 330 L 6 R1

a:Size  
b:Vertical to the vertical form, 'H' is to the horizontal form  
c:Inductance Value[101:100uH;102:1000uH;103:10000uH]  
d:Positive and negative tolerances[K:±10%;L:±15%;M:±20%]  
e:Rated current[0R2:0.2A;1R2:1.2A;10R2:12A]

## ELECTRICAL CHARACTERISTICS

| Part Number          | Inductance [uH] at 20°C | D.C. Resistance [Ω] Typ at 20°C | Rated current [A] | Inductance [uH] @Rated | Dimension A Nom | Dimension B Nom | Dimension C Nom |
|----------------------|-------------------------|---------------------------------|-------------------|------------------------|-----------------|-----------------|-----------------|
| FA2111HT-V/H-100L9R9 | 10                      | 0.012                           | 9.9               | 7.6                    | 8.4             | 19.3            | 1.10            |
| FA2111HT-V/H-120L9R6 | 12                      | 0.013                           | 9.6               | 9.0                    | 8.4             | 19.3            | 1.10            |
| FA2111HT-V/H-150L9R1 | 15                      | 0.014                           | 9.1               | 11.0                   | 8.4             | 19.3            | 1.10            |
| FA2111HT-V/H-180L8R6 | 18                      | 0.016                           | 8.6               | 13.0                   | 8.4             | 19.3            | 1.10            |
| FA2111HT-V/H-220L7R7 | 22                      | 0.020                           | 7.7               | 16.6                   | 8.1             | 19.0            | 1.00            |
| FA2111HT-V/H-270L6R4 | 27                      | 0.025                           | 6.4               | 20.1                   | 8.1             | 19.0            | 0.90            |
| FA2111HT-V/H-330L6R1 | 33                      | 0.028                           | 6.1               | 24.0                   | 8.1             | 19.0            | 0.90            |
| FA2111HT-V/H-390L5R9 | 39                      | 0.030                           | 5.9               | 28.0                   | 8.1             | 19.0            | 0.80            |
| FA2111HT-V/H-470L5R6 | 47                      | 0.030                           | 5.6               | 33.1                   | 8.9             | 20.0            | 0.80            |
| FA2111HT-V/H-560L5R3 | 56                      | 0.035                           | 5.3               | 38.5                   | 8.9             | 20.0            | 0.80            |
| FA2111HT-V/H-680L5R1 | 68                      | 0.040                           | 5.1               | 46.0                   | 8.9             | 20.0            | 0.80            |
| FA2111HT-V/H-820L4R8 | 82                      | 0.045                           | 4.8               | 54.0                   | 8.9             | 20.0            | 0.80            |
| FA2111HT-V/H-101L4R6 | 100                     | 0.050                           | 4.6               | 64.5                   | 8.9             | 20.0            | 0.80            |
| FA2111HT-V/H-121L3R5 | 120                     | 0.08                            | 3.5               | 84.4                   | 8.6             | 19.5            | 0.70            |
| FA2111HT-V/H-151L3R3 | 150                     | 0.10                            | 3.3               | 102.8                  | 8.6             | 19.5            | 0.70            |
| FA2111HT-V/H-181L3R1 | 180                     | 0.12                            | 3.1               | 120.7                  | 8.6             | 19.5            | 0.70            |
| FA2111HT-V/H-221L3R0 | 220                     | 0.13                            | 3.0               | 144.2                  | 8.6             | 19.5            | 0.70            |
| FA2111HT-V/H-271L2R8 | 270                     | 0.14                            | 2.8               | 172.6                  | 8.9             | 20.0            | 0.70            |
| FA2111HT-V/H-331L2R7 | 330                     | 0.16                            | 2.7               | 206.0                  | 8.9             | 20.0            | 0.70            |
| FA2111HT-V/H-391L2R1 | 390                     | 0.22                            | 2.1               | 266.7                  | 8.4             | 19.3            | 0.55            |
| FA2111HT-V/H-471L2R0 | 470                     | 0.28                            | 2.0               | 314.4                  | 8.9             | 19.3            | 0.55            |
| FA2111HT-V/H-561L1R9 | 560                     | 0.32                            | 1.9               | 366.9                  | 8.9             | 20.0            | 0.55            |
| FA2111HT-V/H-681L1R8 | 680                     | 0.35                            | 1.8               | 432.0                  | 8.9             | 20.0            | 0.50            |
| FA2111HT-V/H-821L1R7 | 820                     | 0.39                            | 1.7               | 512.0                  | 9.4             | 20.5            | 0.55            |
| FA2111HT-V/H-102L1R6 | 1000                    | 0.43                            | 1.6               | 608.2                  | 9.4             | 20.5            | 0.55            |

## TECHNICAL INFORMATION



DIMENSIONS:MM