



P/N: FA3216-V-681L3R8




Outline Dimensions(Unit:mm)



Orthographic view




Side view



Winding Construction


Electronical Schematic




Electrical Characteristics(at 25°C)

Inductance : L0A= 680H±15%,at 1KHz,0.3V.
L3.8A= 294uH±15%,at 1KHz,0.3V.
Rated current: 3.8Amps.
D.C.Resistance : 0.120 ohms Typ.

Inductance VS Current



Recommended Soldering Temperature Graph.



	Standard Profile	Standard Profile
Pre-heating	150~180°C,90s±30s	
Heating	above 220°C,30s-60s	above 240°C,30s Max
Peak temperature	245°C±3°C	260°C,10s
Cycle of reflow	2 times	2 times

List of UL Certificate:

Part Name	Mat'l Description	Supplier	UL Number
Copper wire	2UEW-F/155C	Elektrisola Hangzhou Co Ltd	E258243
Core	Iron Powder Cores	KeDa Magneto Electricity	N/A

				Tianchang Fuan Electronic Co Ltd www.fuantronics.net TEL: +86-550-7814888 FAX:+86-550-7831133	 Tolerances unless otherwise specified: (.X)±0.50 (.XX)±0.25 Unit of measurement: mm	Make: Qiumei.Liu	DRAWING TITLE HIGH CURRENT TOROID INDUCTORS	Customer P/N:
						Checked: Beson. zhan		Document/Rev: 00
						Approved: Anson. zhan		Specification Sheet: 1 of 1
REV	DESCRIPTION	APPD	DATE					Material Number: A31DM106S220