

AAQ150



Product Features

- Efficiency up to 93%, PF>0.97, THD<7%
- Full power output is possible over a wide output voltage range
- Constant Current output
- Output current is manually adjustable
- 3 in 1 Dimming Function: 0-10V、PWM、 Resistor
- Lightning protection level : Difference module 6kV , Common mode 15 kV
- Comprehensive protection: input undervoltage, over-temperature, short circuit, dimming interface over-voltage, anti-reverse connection
- IP67 rating for indoor and outdoor
- Warranty: 5 Years



Technical data

Product model	Max. output Power (W)	Input Voltage (Vdc)	Output current (mA)	Output Voltage (Vdc)	PF	Efficiency	size/mm
AAQ150-56-C4170	150	120-277	2670-4170	25-56	0.97	91.5%	186*63*32
AAQ150-56-C4170-S	150	120-277	2670-4170	25-56	0.97	91.5%	186*63*32
AAQ150-214-C1050	150	120-277	700-1050	95-214	0.97	93%	186*63*32
AAQ150-214-C1050-S	150	120-277	700-1050	95-214	0.97	93%	186*63*32

※The model number does not have a tail vertebral letter to indicate the basic model
※The '-S' Indicates with dimming function
※If you have other parameter requirements, you can consult the corresponding sales staff

Technical data

Electrical Specifications

category	project	Technical Indicators
Input parameters	Rated input voltage	120-277VAC
	Input voltage range	108-305VAC
	Input frequency range	47-63HZ
	Input current	1.5A @120Vac, Full Load
	Input power	180W @120Vac, Full Load
	Input surge current peak value	45A @120Vac, Cold Start 70A @230Vac, Cold Start 80A @277Vac, Cold Start
	Power factor	0.99 @120Vac, Full Load 0.97 @230Vac, Full Load 0.95 @277Vac, Full Load 0.9 @120-277Vac 50/60Hz, 70-100% Load
	Total harmonic distortion	7% @120Vac, Full Load 9% @230Vac, Full Load 12% @277Vac, Full Load 15% @120-277Vac 50/60Hz, 70-100% Load
Output parameters (AAQ150-56-4170/-S)	Rated output current	2670-4170mA
	Adjustable current range	1800-4200mA @Ref. AOE curve
	Output voltage range	25-56Vdc @At the rated output voltage, the maximum
	Rated output voltage	36-56Vdc output power Po=Vo*Io=150W
	Default factory output current	2.67A
	Maximum no-load output voltage	80V
	Efficiency	88.0% @Input 120Vac, Output 36V/4.17A 90.5% @Input 230Vac, Output 36V/4.17A 91.0% @Input 277Vac, Output 36V/4.17A 89.0% @Input 120Vac, Output 56V/2.67A 91.5% @Input 230Vac, Output 56V/2.67A 92.0% @Input 277Vac, Output 56V/2.67A
	Current accuracy	±5% @100% load Constant Power Range
	Output current ripple	10% @ΔI=Ipk-pk/2/Io*100%
	Startup current overshoot	10% @LED Load
	Startup time	300~1000ms @100%Load@120-277Vac
	Linear regulation rate	±3% @100%Load
	Load regulation rate	±3% @100%Load
	Over temperature protection	90°C @Casing temperature: Prolonged operation atthe highest temperature will reduce the reliability of the power supply. Pay attention to heat dissipation when in use
	Short circuit protection	20W @Not damaged by prolonged short circuits, automatic recovery upon fault resolution
	Input undervoltage protection	96-108V @ Derating output, which returns to normal after the abnormality is lifted
	Input overvoltage protection	320Vac

category project		Technical Indicators		
Output parameters (AAQ150-214-1050/-S)	Rated output current	700-1050mA		
	Adjustable current range	500-1050mA @Ref. AOE curve		
	Output voltage range	75-143Vdc	@At the rated output voltage, the maximum output power Po=Vo*Io=150W	
	Rated output voltage	95-143Vdc		
	Default factory output current	0.7A		
	Maximum no-load output voltage	250V		
	Efficiency	90.0% @Input 120Vac, Output 143V/1.05A 92.5% @Input 230Vac, Output 143V/1.05A 92.5% @Input 277Vac, Output 143V/1.05A 90.5% @Input 120Vac, Output 214V/0.7A 93.0% @Input 230Vac, Output 214V/0.7A 93.5% @Input 277Vac, Output 214V/0.7A		
	Current accuracy	±5% @100% load Constant Power Range		
	Output current ripple	7% @ΔI=Ipk-pk/2/Io*100%		
	Startup current overshoot	10% @LED Load		
	Startup time	300～1000ms @100%Load@120-277Vac		
	Linear regulation rate	±3% @100%Load		
	Load regulation rate	±3% @100%Load		
	Over temperature protection	90℃	@Casing temperature: Prolonged operation atthe highest temperature will reduce the reliability of the power supply. Pay attention to heat dissipation when in use	
	Short circuit protection	20W	@Not damaged by prolonged short circuits, automatic recovery upon fault resolution	
	Input undervoltage protection	96-108V	@ Derating output, which returns to normal after the abnormality is lifted	
	Input overvoltage protection	320Vac		

Technical data

category	project	Technical Indicators
0-10V Dimming	External voltage range	0-12V @DIM+ output 100uA current
	Recommended dimming voltage	1-10V
	Dimming output range	10-100% @DIM+/DIM-reverse connection prohibited.
	Dimming cutoff voltage	0.45-0.55V @typical 0.5V
	Dimming start voltage	0.6-0.7V @typical 0.65V
PWM Dimming	PWM High	9.8-10.2V @DIM+ output 100uA current
	PWM Low	0-0.3V @DIM+/DIM-reverse connectionprohibited.
	PWM Frequency	500-2000Hz
	Recommended dimming duty cycle	10-100%
	Dimming output range	10-100%
	Dimming cutoff duty cycle	4.5-5.5% @Typical 5%
	Dimming start duty cycle	6-7% @Typical 6.5%
Resistor Dimming	External resistor	0-100KΩ @DIM+ output 100uA current
	Dimming output range	10-100%
	Dimming cutoff resistance	4.5-5.5KΩ @Typical 5KΩ
	Dimming start resistance	6-7KΩ @Typical 6.5KΩ
Interface protection	Interface over voltage protection	400Vdc or 277Vac @Interface not damaged within 30minutes
Environment	Operating temperature	-40...90°C @Typical 60°C
	Operating humidity	10-90%RH @No condensation
	Storage temperature	-40...90°C @Typical 25°C
	Storage humidity	10-90%RH @No condensation
Other	Estimation of Mean Time Between Failures (MTBF)	250000 hours @230Vac, full load, ambient temperature 25°C
	Lifetime	50,000 hours @230Vac, full load, Tc=75°C
	International Protection	IP67 @Suitable for dry and humid environments, avoid prolonged exposure to rain
	Maximum casing temperature	90°C
	Warranty	5 Years @Casing temperature (Tc point) not exceeding 75°C
	We ght	750g @Net weight
	Dimension	186mm*63mm*32mm

Remarks:


1. The dimming interface can withstand voltages within 277Vac for a short period of time (within 30 minutes) without damage, and returns to normal after the fault is resolved; when the dimming interface is connected to AC mains power, the output current drops to half of the set current value. Construction workers can quickly identify and resolve faults based on this phenomenon to avoid permanent damage to the interface;
2. All performance parameters are typical values measured at an ambient temperature of 25°C and using an LED load, unless otherwise specified;
3. When the dimming line is not in use, please seal the dimming line connector with an insulating sleeve to prevent interference signals from causing damage to the dimming line and affecting the normal operation of the power supply;

category project		Technical Indicators
Safety and EMC	CCC	GB 19510.14-2009、 GB/T 17743-2021、 GB 17625.1-2022
	ENEC	EN 61347-1:2015 EN 61347-2-13:2014 EN 61347-2-13:2014/A1:2017
	CB	IEC 61347-1, IEC 61347-2-13-2016
	CE	EN 61347-2-13:2014 EN61347- 1:2008+A1:2011+A2:2013
	UL	UL8750
	Conducted emission	EN 55015/GB 17743 @Conducted emission Test &Radiated emission Test
	Radiated emission	FCC Part 15 Subpart B
	Harmonics Current	EN 61000-3-2 @Harmonic current emissions
	Voltage flicker	EN 61000-3-3 @Voltage Fluctuations & Flicker
	ESD	EN 61000-4-2 @Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
	Radiated Susceptibility	EN 61000-4-3 @Radio-Frequency Electromagnetic Field Susceptibility Test-RS
	Surge (transient)	EN 61000-4-5 @Surge Immunity Test:Differential Mode 6 kV, Common Mode 15 kV
	Conducted immunity	EN 61000-4-6 @Conducted Radio Frequency Disturbances Test-CS
	Power frequency magnetic field	EN 61000-4-8 @Power Frequency Magnetic Field Test
	Voltage dips and interruption	EN 61000-4-11 @Voltage Dips
	Immunity of lighting equipment	EN 61547 @Electromagnetic Immunity Requirements Applies To Lighting Equipment
	Oscillatory wave immunity	EN 61000-4-12 @Oscillatory Waves Immunity Test
	Insulation	I/P-O/P, I/P-FG, O/P-FG:100MΩ / 500VDC / 25°C/70% RH
	Dielectric strength	I/P-O/P:3.75kVac I/P-FG:1.5kVac O/P-FG:500Vac I/P-DIM&Vaux:3.75kVac O/P-DIM&Vaux:1.5kVac DIM&Vaux-FG:1.5kV
	Ground resistance	<0.1Ω, 25A/1min
	Leakage current	<0.75mA 277Vac


Product datasheet

Exterior dimensions (unit: mm)

Note: AAQ150-****




Note: AAQ150-****-S




Characteristic curves

Vin	Peak current	Duration (@10% peak current)	Duration (@50% peak current)
120Vac	45A	685us	205us
230Vac	70A	695us	210us
277Vac	80A	650us	215us




Characteristic curves

Efficiency vs Output voltage




Efficiency vs Output voltage




Characteristic curves


PF vs Output power




PF vs Output power




THD vs Output power




THD vs Output power



Output voltage vs Output current




Output voltage vs Output current




Characteristic curves


Output power VS Input voltage



Output power VS Dimming signal



Output power vs TC temperature



Lifespan vs TC temperature

